



Myers - Predator

Model	hp	gpm	stg	3 Wire	
				2 Wire	w/o CB*
ST5-8	1/2	8	9	\$631.00	\$554.00
ST7-8	3/4	8	12	836.00	753.00
ST10-8	1	8	15	969.00	887.00
ST15-8	1-1/2	8	20	1335.00	1216.00
ST5-12	1/2	12	7	599.00	520.00
ST7-12	3/4	12	9	777.00	694.00
ST10-12	1	12	11	881.00	798.00
ST15-12	1-1/2	12	16	1244.00	1127.00
ST5-20	1/2	20	4	755.00	677.00
ST7-20	3/4	20	6	830.00	747.00
ST10-20	1	20	8	869.00	784.00
ST15-20	1-1/2	20	11	1189.00	1071.00
ST10-25	1	25	7	1029.00	946.00
ST15-25	1-1/2	25	9	1245.00	1128.00

Myers - Rustler II

Model	hp	gpm	stg.	3Wire	
				2 Wire	w/oCB*
N5-8	1/2	8	9	\$585.00	\$510.00
N7-8	3/4	8	12	740.00	656.00
N10-8	1	8	15	881.00	798.00
N15-8	1-1/2	8	20	1123.00	1006.00
N5-12	1/2	12	7	530.00	452.00
N7-12	3/4	12	9	666.00	582.00
N10-12	1	12	11	772.00	691.00
N15-12	1-1/2	12	16	1012.00	895.00
N10-20	1	20	8	740.00	656.00
N15-20	1-1/2	20	11	959.00	841.00

Pump Performance Charts:

- **30/50 Pressure Setting**
- **Values Listed are suggested manufacturer's operating ranges**
- **2 & 3 Wire, 115V & 230V Models**
- **Please call for special conditions or engineering help**

	Pressure		Depth of Water (feet)															
	PSI		20	40	60	80	100	120	140	160	180	200	220	240	260	300	340	380
8 GPM																		
ST5/N5	30/50	12	11.4	10.8	10.1	9.3	8.3	7.2	5.8									
ST7/N7	30/50				11.5	11.1	10.6	10	9.5	8.8	8	7.1	6.1	4.9				
ST10/N10	30/50						11.4	11.3	10.9	10.5	10	9.5	9.0	8.4	7.8	7.0	6.2	
12 GPM																		
ST5/N5	30/50		14.5	13	11.5	9.8	7	2										
ST7/N7	30/50			15.5	14.5	13.4	12.2	10.9	9.4	7.5								
ST10/N10	30/50					15.3	14.5	13.5	12.6	11.6	10.5	9.2	7.5					
ST15/N15	30/50									15.4	14.9	14.3	13.7	13.1	11.7	10.2	8.3	
20 GPM																		
ST7/N7	30/50	21.5	19.5	16														
ST10/N10	30/50	24	23	21.5	20	17.5	14.5											
ST15/N15	30/50			24.5	23.5	22.5	21.5	20	18.5	16.5	14.5	12.5						