



Flint and Walling "G" Series

Model	hp	gpm	stg	2 Wire	3 Wire w/o CB*
4F05G05	1/2	5	15	\$712.00	\$664.00
4F07G05	1/2	7	10	625.00	577.00
4F07G07	3/4	7	14	755.00	695.00
4F10G05	1/2	10	8	543.00	495.00
4F10G07	3/4	10	12	702.00	642.00
4F10G10	1	10	15	849.00	775.00
4F19G10	1	19	9	818.00	744.00
4F27G10	1	27	7	790.00	716.00

Flint and Walling "S" Series

Model	hp	gpm	stg	2 Wire	3 Wire w/o CB*
4F05S05	1/2	5	15	\$838.00	\$790.00
4F05S07	3/4	5	21	994.00	934.00
4F07S05	1/2	7	10	734.00	686.00
4F07S07	3/4	7	14	908.00	848.00
4F10S05	1/2	10	8	670.00	622.00
4F10S07	3/4	10	12	863.00	803.00
4F10S10	1	10	15	974.00	900.00
4F19S07	3/4	19	7	866.00	806.00
4F19S10	1	19	9	938.00	864.00
4F19S15	1 1/2	19	12	1148.00	1044.00
4F27S07	3/4	27	6	862.00	802.00
4F27S10	1	27	7	922.00	848.00
4F27S15	1 1/2	27	10	1122.00	1018.00

Pump Performance Charts:

- 30/50 Pressure Setting
- Values Listed are suggested manufacturer's operating ranges
- 2 & 3 Wire, 115V & 230V Models
- Please call for special conditions or engineering help

	Pressure		Depth (in Ft.)														
	PSI		20	40	60	80	100	125	150	175	200	225	250	275	300	350	400
5GPM																	
4F05-05	30/50		8.3	7.9	7.5	7.1	6.7	6.2	5.5	4.9	4.2						
4F05-07	30/50			8.7	8.5	8.2	7.8	7.5	7.0	6.9	6.5	6.2	5.7	5.3	4.4		
7 GPM																	
4F07-05	30/50	11.3	10.7	10.0	9.3	8.5	8.0	7.0	5.0								
4F07-07	30/50		12.2	11.8	11.3	10.9	10.5	9.8	9.0	8.0	7.2	6.3	5.3				
10 GPM																	
4F10-05	30/50	12.8	12.0	11.0	10.0	8.7											
4F10-07	30/50	14.3	13.8	13.3	12.8	12.4	11.5	10.5	9.8	8.9	7.9						
4F10-10	30/50	14.9	14.5	14.1	13.7	13.3	12.5	12.0	11.5	10.9	10.3	9.5	8.6	7.9			
19 GPM																	
4F19-07	30/50	20.6	18.7	16.6													
4F19-10	30/50	22.5	21.2	19.8	18.4	16.8	15.0	12.5									
4F19-15	30/50	24.2	23.2	22.4	21.4	20.5	19.0	17.5	17.0	14.0	12.0						
27 GPM																	
4F27-07	30/50	25.0	22.0	18.0	12.0												
4F27-10	30/50	28.0	25.0	23.0	19.0	15.0											
4F27-15	30/50	31.0	30.0	28.0	27.0	25.0	22.0	20.0	17.0	11.0							